

**315**

**Protočni senzor sa magnetnim kontaktom.**



230 V - 0,02 A.  
 Pmax radni: 6 bar.  
 Tmax radna: 100°C.  
 Kontakti se zatvaraju sa porastom protoka: 156 l/h (1/2") i 456 l/h (3/4").  
 Kontakti se otvaraju sa padom protoka: 108 l/h (1/2") i 348 l/h (3/4").



Art			
315400	1/2"	1	50
315500	3/4"	1	25

**558**

**Automatski ventil za ekspanzionu posudu.**



Pmax radni: 10 bar.  
 Tmax radna: 110°C.

Art			
558500	3/4"	1	50

**558**

**Automatski ventil za ekspanzionu posudu.**



Sa ispusnom slavinom.  
 Pmax radni: 10 bar.  
 Tmax radna: 110°C.

Art			
558510	3/4"	1	50

**626**

**Senzor protoka.**



Za cevi od 1" do 8".  
 240 V - 15(7) A.  
 Klasa zaštite: IP 54.  
 Tmax - Tmin: -30÷120°C.



Art			
626600	1"	1	5
626009	komplet lamela	1	-

**5580**

**Loptasti ventil za ekspanzionu posudu.**



Sa ispusnom slavinom.  
 Pmax radni: 6 bar.  
 Tmax radna: 85°C.

Art			
558050	3/4"	1	50
558060	1"	1	50
558070	1 1/4"	1	20

**538**

**Slavina za punjenje i pražnjenje.**



Sa čepom i nastavkom za crevo.  
 Pmax radni: 10 bar.  
 Tmax radna: 100°C.

Art			
538400	1/2" M	1	100

**Aplikaciona šema loptastog ventila serije 5580.**

