



Visina (mm)	Oсно rastojanje (mm)	TIP	Širina (mm)	Težina Kg/(m)	Sadržaj vode (l/m)	Dostupne dužine (mm)
300	245	10	50	7.6	1.7	400 - 2000
		11	50	8.9	1.7	400 - 2000
		21	70	15.8	3.4	400 - 3000
		22	106	17.2	3.4	400 - 3000
		33	164	25.6	5.1	400 - 1900
400	345	10	50	9.6	2.1	400 - 2000
		11	50	11.5	2.1	400 - 2000
		21	70	20.8	4.3	400 - 3000
		22	106	22.7	4.3	400 - 3000
		33	164	33.4	6.4	400 - 1900
500	445	10	50	12.1	2.6	400 - 2000
		11	50	14.6	2.6	400 - 2000
		21	70	25.9	5.2	400 - 3000
		22	106	28.4	5.2	400 - 3000
		33	164	39.8	7.8	400 - 1900
600	545	10	50	14.5	3.1	400 - 2000
		11	50	17.6	3.1	400 - 2000
		21	70	30.7	6.2	400 - 3000
		22	106	33.6	6.2	400 - 3000
		33	164	50.5	9.3	400 - 1900
900	845	10	50	20.6	4.1	400 - 2000
		11	50	25.5	4.1	400 - 2000
		21	70	46.1	8.2	400 - 3000
		22	106	51.0	8.2	400 - 3000
		33	164	75.9	12.3	400 - 1900
Ispitni pritisak	Radni pritisak (statički pritisak+pritisak pumpe)				Max. radna temperatura	
13 Bar	10 Bar				120 °C	